



SIMATIC ET 200SP, Analog input module, AI 4xRTD/TC High Feature, suitable for BU type A0, A1, Color code CC00, channel diagnostics, 16 bit, +/-0.1%, 2-/3-/4-wire

General information	
Product type designation	AI 4xRTD/TC 2-/3-/4-wire HF
Firmware version	V2.1
<ul style="list-style-type: none"> <li>FW update possible</li> </ul>	Yes
usable BaseUnits	BU type A0, A1
Color code for module-specific color identification plate	CC00
Product function	
<ul style="list-style-type: none"> <li>I&amp;M data</li> </ul>	Yes; I&M0 to I&M3
<ul style="list-style-type: none"> <li>Isochronous mode</li> </ul>	No
<ul style="list-style-type: none"> <li>Adjustment of measuring range</li> </ul>	Yes
Engineering with	
<ul style="list-style-type: none"> <li>STEP 7 TIA Portal configurable/integrated from version</li> </ul>	V12 SP1 / V13
<ul style="list-style-type: none"> <li>STEP 7 configurable/integrated from version</li> </ul>	V5.5 SP3 / V5.5 SP4
<ul style="list-style-type: none"> <li>PCS 7 configurable/integrated from version</li> </ul>	V8.1 SP1
<ul style="list-style-type: none"> <li>PROFIBUS from GSD version/GSD revision</li> </ul>	GSD Revision 5
<ul style="list-style-type: none"> <li>PROFINET from GSD version/GSD revision</li> </ul>	GSDML V2.3
CiR - Configuration in RUN	
Reparameterization possible in RUN	Yes
Calibration possible in RUN	Yes
Supply voltage	
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Reverse polarity protection	Yes
Power loss	
Power loss, typ.	0.75 W
Address area	
Address space per module	
<ul style="list-style-type: none"> <li>Address space per module, max.</li> </ul>	8 byte; + 1 byte for QI information
Hardware configuration	
Automatic encoding	
<ul style="list-style-type: none"> <li>Type of mechanical coding element</li> </ul>	Type A
Analog inputs	
Number of analog inputs	4
permissible input voltage for voltage input (destruction limit), max.	30 V
Constant measurement current for resistance-type transmitter, typ.	2 mA
Cycle time (all channels), min.	Sum of the basic conversion times and additional processing times (depending on the parameterization of the active channels); for line

compensation in case of a three-wire connection, an additional cycle is necessary

Yes; °C/°F/K

Technical unit for temperature measurement adjustable

**Input ranges (rated values), voltages**

- -1 V to +1 V
  - Input resistance (-1 V to +1 V)
- -250 mV to +250 mV
  - Input resistance (-250 mV to +250 mV)
- -50 mV to +50 mV
  - Input resistance (-50 mV to +50 mV)
- -80 mV to +80 mV
  - Input resistance (-80 mV to +80 mV)

**Input ranges (rated values), thermocouples**

- Type B
  - Input resistance (Type B)
- Type C
  - Input resistance (Type C)
- Type E
  - Input resistance (Type E)
- Type J
  - Input resistance (type J)
- Type K
  - Input resistance (Type K)
- Type L
  - Input resistance (Type L)
- Type N
  - Input resistance (Type N)
- Type R
  - Input resistance (Type R)
- Type S
  - Input resistance (Type S)
- Type T
  - Input resistance (Type T)
- Type U
  - Input resistance (Type U)
- Type TXK/TXK(L) to GOST
  - Input resistance (Type TXK/TXK(L) to GOST)

**Input ranges (rated values), resistance thermometer**

- Cu 10
  - Input resistance (Cu 10)
- Ni 100
  - Input resistance (Ni 100)
- Ni 1000
  - Input resistance (Ni 1000)
- LG-Ni 1000
  - Input resistance (LG-Ni 1000)
- Ni 120
  - Input resistance (Ni 120)
- Ni 200
  - Input resistance (Ni 200)
- Ni 500
  - Input resistance (Ni 500)
- Pt 100
  - Input resistance (Pt 100)
- Pt 1000
  - Input resistance (Pt 1000)
- Pt 200
  - Input resistance (Pt 200)
- Pt 500
  - Input resistance (Pt 500)

**Input ranges (rated values), resistors**

- 0 to 150 ohms
  - Input resistance (0 to 150 ohms)
- 0 to 300 ohms

<ul style="list-style-type: none"> <li>— Input resistance (0 to 300 ohms)</li> </ul>	1 M $\Omega$
<ul style="list-style-type: none"> <li>• 0 to 600 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 600 ohms)</li> </ul> </li> </ul>	Yes; 15 bit 1 M $\Omega$
<ul style="list-style-type: none"> <li>• 0 to 3000 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 3000 ohms)</li> </ul> </li> </ul>	Yes; 15 bit 1 M $\Omega$
<ul style="list-style-type: none"> <li>• 0 to 6000 ohms <ul style="list-style-type: none"> <li>— Input resistance (0 to 6000 ohms)</li> </ul> </li> </ul>	Yes; 15 bit 1 M $\Omega$
<ul style="list-style-type: none"> <li>• PTC <ul style="list-style-type: none"> <li>— Input resistance (PTC)</li> </ul> </li> </ul>	Yes; 15 bit 1 M $\Omega$
<b>Thermocouple (TC)</b>	
Temperature compensation	
<ul style="list-style-type: none"> <li>— parameterizable</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— Reference channel of the module</li> </ul>	Yes
<ul style="list-style-type: none"> <li>— internal comparison point</li> </ul>	Yes; with BaseUnit type A1
<ul style="list-style-type: none"> <li>— Number of reference channel groups</li> </ul>	4; Group 0 to 3
<b>Cable length</b>	
<ul style="list-style-type: none"> <li>• shielded, max.</li> </ul>	200 m; 50 m with thermocouples
<b>Analog value generation for the inputs</b>	
Measurement principle	integrating (Sigma-Delta)
Integration and conversion time/resolution per channel	
<ul style="list-style-type: none"> <li>• Resolution with overrange (bit including sign), max.</li> </ul>	16 bit
<ul style="list-style-type: none"> <li>• Integration time, parameterizable</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• Basic conversion time, including integration time (ms) <ul style="list-style-type: none"> <li>— additional processing time for wire-break check</li> </ul> </li> </ul>	2 ms; In the ranges resistance thermometers, resistors and thermocouples
<ul style="list-style-type: none"> <li>— additional power line wire-break check</li> </ul>	2 ms; for 3/4 wire transducer (resistance thermometer and resistor)
<ul style="list-style-type: none"> <li>• Interference voltage suppression for interference frequency <math>f_1</math> in Hz</li> </ul>	16.6 / 50 / 60 Hz
<ul style="list-style-type: none"> <li>• Conversion time (per channel)</li> </ul>	180 / 60 / 50 / (67.5 / 22.5 / 18.75) ms
Smoothing of measured values	
<ul style="list-style-type: none"> <li>• Number of smoothing levels</li> </ul>	4; None; 4/8/16 times
<ul style="list-style-type: none"> <li>• parameterizable</li> </ul>	Yes
<b>Encoder</b>	
Connection of signal encoders	
<ul style="list-style-type: none"> <li>• for voltage measurement</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for resistance measurement with two-wire connection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for resistance measurement with three-wire connection</li> </ul>	Yes
<ul style="list-style-type: none"> <li>• for resistance measurement with four-wire connection</li> </ul>	Yes
<b>Errors/accuracies</b>	
Linearity error (relative to input range), (+/-)	0.01 %; $\pm 0.1$ % for resistance thermometers and resistance
Temperature error (relative to input range), (+/-)	0.0009 %/K; $\pm 0.005$ % / K at thermocouple
Crosstalk between the inputs, min.	-50 dB
Repeat accuracy in steady state at 25 °C (relative to input range), (+/-)	0.05 %
Operational error limit in overall temperature range	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> </ul>	0.1 %
<ul style="list-style-type: none"> <li>• Resistance, relative to input range, (+/-)</li> </ul>	0.1 %
Basic error limit (operational limit at 25 °C)	
<ul style="list-style-type: none"> <li>• Voltage, relative to input range, (+/-)</li> </ul>	0.05 %
<ul style="list-style-type: none"> <li>• Resistance, relative to input range, (+/-)</li> </ul>	0.05 %
Interference voltage suppression for $f = n \times (f_1 \pm 1 \%)$ , $f_1 =$ interference frequency	
<ul style="list-style-type: none"> <li>• Series mode interference (peak value of interference &lt; rated value of input range), min.</li> </ul>	70 dB; With conversion time 67.5 / 22.5 / 18.75 ms: 40 dB
<ul style="list-style-type: none"> <li>• Common mode voltage, max.</li> </ul>	10 V
<ul style="list-style-type: none"> <li>• Common mode interference, min.</li> </ul>	90 dB
<b>Interrupts/diagnostics/status information</b>	
Alarms	
<ul style="list-style-type: none"> <li>• Limit value alarm</li> </ul>	Yes; two upper and two lower limit values in each case
Diagnoses	
<ul style="list-style-type: none"> <li>• Monitoring the supply voltage</li> </ul>	Yes

- Wire-break Yes; channel by channel
- Group error Yes
- Overflow/underflow Yes; channel by channel

#### Diagnostics indication LED

- Monitoring of the supply voltage (PWR-LED) Yes; green PWR LED
- Channel status display Yes; green LED
- for channel diagnostics Yes; red LED
- for module diagnostics Yes; green/red DIAG LED

#### Ambient conditions

##### Ambient temperature during operation

- horizontal installation, min. -30 °C; < 0 °C as of FS08
- horizontal installation, max. 60 °C
- vertical installation, min. -30 °C; < 0 °C as of FS08
- vertical installation, max. 50 °C

#### Dimensions

Width	15 mm
Height	73 mm
Depth	58 mm

**last modified:** 12/28/2021 