

OTL50-2 black 2xAl/Cu 1,5-50mm² 1000V Universal terminal

| | |
|---------------------------------------|--------------------------------------|
| SKU | MAA2050S10 |
| EAN | 4744397014092 |
| Color | Black |
| Wire material | Al/Cu |
| Cross-section min. (mm ²) | 1,5 |
| Cross-section max. (mm ²) | 50 |
| Input wire min. (mm ²) | 1,5 |
| Input wire max. (mm ²) | 50 |
| Output wire min. (mm ²) | 1,5 |
| Output wire max. (mm ²) | 50 |
| Number of connections | 4 |
| Nominal current (A) | 320 (Cu) / 290 (Al) |
| Nominal voltage (V) | 1000 |
| Service temperature (°C) | 80 |
| Material | Tin-plated aluminium, polyamide PA66 |
| Mounting method | DIN rail |
| Item width (mm) | 30 |
| Item length (mm) | 49 |



| | |
|-------------------------------|---|
| Item height (mm) | 43 |
| Item weight (g) | 90 |
| Screw | Hex 5 |
| Tightening torque (Nm) | 1,5 Nm (1,5 - 2,5 mm ²) 5 Nm (4 - 10 mm ²) 10 Nm (16 - 50 mm ²) |
| IP rating | IP20 |
| Certification | EN 61238-1; EN60947-7-1 |
| Flame resistance | UL94 V0 |
| CN8 code | 85369010 |
| Package quantity (pcs) | 15 |